TREX[®] SIGNATURE PANELS[®]

Basic Installation Instructions

Trex

TOOLS NEEDED



» NOTES:

2

These are not detailed instructions. Refer to trex.com full installation guide for additional installation methods.

- » Assembled Trex Signature Panels **DO NOT** come with foot blocks. You must purchase foot blocks separately (sku BKALFTBLK) (one per panel required on spans greater than 6').
- » Assembled Trex Signature Panels DO NOT come with brackets and screws. You must purchase the horizontal rail hardware separately (sku BKFHBKTALPNL) (one per panel).

33-15/16"

(86.2 cm)

or

39-15/16" (101.4 cm) from decking surface

Attach Brackets to Posts



NOTE: Optional measurement: Measure 1-3/8" (3.5 cm) from top of post base plate.



Cutting Rail Insert



How to Measure and Cut Top Rail for Post-to-Post Configuration



Cutting Top Rail Cover



Have Questions? 1-800-BUY-TREX **NOTE:** Construction methods are always improving. Please ensure you have the most up-to-date installation instructions by visiting: **trex.com**

Basic Installation Instructions

Attaching Foot Block (when required)

(One Foot Block is required for all spans over 6')





Place Adhesive Strip



NOTE: Make sure surface is clean and dry.

10 7/64" (2.8 mm)

GENTLE tapping with a **rubber mallet** may facilitate fastening.

REFER TO FULL INSTRUCTIONS FOR ATTACHMENT OF DIFFERENT RAILING CONFIGURATIONS, ATTACHMENT OF POST CAPS, BRACKET COVERS, SKIRTS, AND FOOTBLOCKS.







